

54  
Claims

- 1 1. A method of calibrating a plurality of seismic sensors, each sensor having  
2 an axis of sensitivity, comprising:  
3 coupling the sensors with each sensor positioned with its axis of  
4 sensitivity in a different spatial direction;  
5 rotating the sensors;  
6 measuring one or more output signals from the sensors;  
7 processing the output signals from the sensors; and  
8 storing one or more calibration coefficients.
- 1 2. The method of claim 1, wherein the sensors comprise micro-machined  
2 accelerometers.
- 1 3. The method of claim 1, wherein coupling the sensors with each sensor  
2 positioned with its axis of sensitivity in a different spatial direction  
3 comprises, coupling the sensors with the axes of sensitivity in:  
4 a first direction;  
5 a second direction; and  
6 a third direction.
- 1 4. The method of claim 1, wherein rotating the sensors comprises, rotating  
2 the sensors about the x-axis, the y-axis and the z-axis.
- 1 5. The method of claim 1, wherein measuring one or more output signals  
2 from the sensors comprises, measuring the output signals from the  
3 sensors at one or more angles of rotation.
- 1 6. The method of claim 1, wherein processing the output signals from the  
2 sensors comprises, calculating one or more calibration coefficients from  
3 the measured output signals of the sensors.

T044T 2244T 660

ADT 2A ADT

RET/US 00/06032  
IPET/US 20 MAR 200

00014422-11441

- 1 7. The method of claim 1, wherein each sensor further includes a corresponding  
2 ASIC having a local non-volatile memory; and wherein storing one or more  
3 calibration coefficients includes storing the corresponding calibration  
4 coefficients to the corresponding local non-volatile memories.
- 1 8. The method of claim 1, wherein storing one or more calibration coefficients  
2 includes storing the corresponding calibration coefficients to an external  
3 database.
- 1 9. The method of claim 1, wherein coupling, rotating, measuring, and processing  
2 are provided in accordance with the Institute of Electrical and Electronic  
3 Engineers Specification IEEE 337-1972 for the IEEE Standard Specification  
4 Format Guide and Test Procedure for Linear, Single-Axis, Pendulous, Analog  
5 Torque Balance Accelerometer.
- 1 10. The method of claim 1, wherein the seismic sensor further comprises a proof  
2 mass, the method further comprising controlling the position of the proof mass  
3 at two or more locations using an electronic signal.
- 1 11. The method of claim 10 further comprising correcting seismic sensor non-  
2 linear characteristics using the positioning of the proof mass.
- 1 12. The method of claim 11 further comprising determining a proof mass control  
2 setting indicative of the mass position for correcting the non-linear  
3 characteristics and storing the control setting.
- 1 13. The method of claim 5, wherein the seismic sensor further comprises a proof  
2 mass, the method further comprising controlling the position of the proof mass  
3 at two or more locations using an electronic signal and measuring the position  
4 of the proof mass at two or more positions.

55

*DET/US 00/060320*  
*IPET/US 20 MAR 2001*

- 1 14. The method of claim 7, wherein the seismic sensor further comprises a proof  
2 mass, the method further comprising controlling the position of the proof mass  
3 at two or more locations using an electronic signal, determining a proof mass  
4 control setting indicative of a mass position for correcting seismic sensor non-  
5 linear characteristics, and storing the control setting.

*add #1*

FOI b 7 - 2244660

*56*